


DELIVERY PROGRAM

Standard-Delivery **Mineral Insulated Thermocouple Cable**



Type: K, N, J

Outer sheath material: e.g 2.4816 Inc. 600, 1.4571, 1.4301, 1.4550 etc.

Please, select here the desired type:

Mineral insulated 2-core Thermocouple Cable standard range acc. to IEC 61515

Outside Diameter (mm)	Tolerances (mm)	Min. diameter of wire (mm)	Wall Thickness (mm)
0,50	± 0,025	0,08	0,05
1,00	± 0,025	0,15	0,10
1,50	± 0,025	0,23	0,15
1,60	± 0,025	0,24	0,16
2,00	± 0,025	0,30	0,20
3,00	± 0,030	0,45	0,30
3,20	± 0,030	0,48	0,32
4,00	± 0,045	0,60	0,40
4,50	± 0,045	0,68	0,45
4,80	± 0,045	0,72	0,48
6,00	± 0,060	0,90	0,60
6,40	± 0,060	0,96	0,64
8,00	± 0,080	1,20	0,80

Special geometries (core diameter, wall thickness, etc.) upon customer requests.

Mineral insulated 4-core Thermocouple Cable standard program

Outside Diameter (mm)	Tolerances (mm)	Min. diameter of wire (mm)	Wall Thickness (mm)
2,00	± 0,025	0,26	0,20
3,00	± 0,030	0,40	0,30
4,50	± 0,045	0,60	0,45
5,00	± 0,045	0,65	0,45
6,00	± 0,060	0,78	0,60
8,00	± 0,080	1,00	0,80

Special geometries (core diameter, wall thickness, etc.) upon customer requests.

subject to errors

ThermCable GmbH
Am Bahnhof 6a
63505 Langenselbold

Mail: info@thermcable.de
Web: www.thermcable.de

Tel. +49 (0) 61 84 / 9 32 84 - 0
Fax +49 (0) 61 84 / 9 32 84 - 11

